

P 系列气动接头

1 适用范围

P 系列气动接头的工作温度 0°C ~ 60°C，工作压力 0~1MPa。P 系列气动接头主要用于气动系统中，通过气管实现气动元件之间的连接。

2 型号及含义

PC - 8 / 01

螺纹型式及尺寸：M5：M5；01：R1/8"；02：R1/4"；03：R3/8"；04：R1/2"；

气管外径：04：Φ4mm；06：Φ6mm；08：Φ8mm；10：Φ10mm；

12：Φ12mm；16：Φ16mm；

型号

* 具体型号规格参考各产品表

2.1 技术要求

使用流体	空气、真空
使用压力范围	0~1MPa
负压	-750mmHg(10Torr)
使用环境及流体温度	0~60°C
适用软管	尼龙及 PU

3 主要规格及技术参数

3.1 气管外径

	公制					
型号	4	6	8	10	12	16
外径	Φ4	Φ6	Φ8	Φ10	Φ12	Φ16

3.2 螺纹型式及尺寸

	锥管螺纹				
型号	01	02	03	04	06
尺寸	R1/8"	R1/4"	R3/8"	R1/2"	R3/4"



型号	
PC-4/M5	PC-8/04
PC-4/01	PC-10/01
PC-4/02	PC-10/02
PC-6/M5	PC-10/03
PC-6/01	PC-10/04
PC-6/02	PC-12/02
PC-6/03	PC-12/03
PC-6/04	PC-12/04
PC-8/01	PC-16/03
PC-8/02	PC-16/04
PC-8/03	



型号	
PCF-4/M5	PCF-8/03
PCF-4/01	PCF-8/04
PCF-4/02	PCF-10/01
PCF-6/M5	PCF-10/02
PCF-6/01	PCF-10/03
PCF-6/02	PCF-10/04
PCF-6/03	PCF-12/02
PCF-6/04	PCF-12/03
PCF-8/01	PCF-12/04
PCF-8/02	



型号	
PL-4/M5	PL-8/04
PL-4/01	PL-10/01
PL-4/02	PL-10/02
PL-6/M5	PL-10/03
PL-6/01	PL-10/04
PL-6/02	PL-12/02
PL-6/03	PL-12/03
PL-6/04	PL-12/04
PL-8/01	PL-16/03
PL-8/02	PL-16/04
PL-8/03	



型号	
PLL-4/M5	PLL-8/04
PLL-4/01	PLL-10/01
PLL-4/02	PLL-10/02
PLL-6/M5	PLL-10/03
PLL-6/01	PLL-10/04
PLL-6/02	PLL-12/02
PLL-6/03	PLL-12/03
PLL-6/04	PLL-12/04
PLL-8/01	PLL-16/03
PLL-8/02	PLL-16/04
PLL-8/03	



型号	
PH-4/M5	PH-8/03
PH-4/01	PH-8/04
PH-4/02	PH-10/-01
PH-6/M5	PH-10/02
PH-6/01	PH-10/03
PH-6/02	PH-10/04
PH-6/03	PH-12/02
PH-6/04	PH-12/03
PH-8/01	PH-12/04
PH-8/02	



型号	
PLF-4/M5	PLF-8/03
PLF-4/01	PLF-8/04
PLF-4/02	PLF-10/01
PLF-6/M5	PLF-10/02
PLF-6/01	PLF-10/03
PLF-6/02	PLF-10/04
PLF-6/03	PLF-12/02
PLF-6/04	PLF-12/03
PLF-8/01	PLF-12/04
PLF-8/02	



型号	
PB-4/M5	PB-8/04
PB-4/01	PB-10/01
PB-4/02	PB-10/02
PB-6/M5	PB-10/03
PB-6/01	PB-10/04
PB-6/02	PB-12/02
PB-6/03	PB-12/03
PB-6/04	PB-12/04
PB-8/01	PB-16/03
PB-8/02	PB-16/04
PB-8/03	



型号	
PX-4/M5	PX-8/03
PX-4/01	PX-8/04
PX-4/02	PX-10/01
PX-6/M5	PX-10/02
PX-6/01	PX-10/03
PX-6/02	PX-10/04
PX-6/03	PX-12/02
PX-6/04	PX-12/03
PX-8/01	PX-12/04
PX-8/02	

<div>PU 直通</div> <div></div>	<div>型号</div> <div>PU-4</div> <div>PU-6</div> <div>PU-8</div> <div>PU-10</div> <div>PU-12</div>	<div>PG 减径直通</div> <div></div>	<div>型号</div> <div>PG-6/4</div> <div>PG-8/6</div> <div>PG-10/8</div> <div>PG-12/10</div>
<div>PV L 型三通</div> <div></div>	<div>型号</div> <div>PV-4</div> <div>PV-6</div> <div>PV-8</div> <div>PV-10</div> <div>PV-12</div> <div>PV-16</div>	<div>PY Y 型三通</div> <div></div>	<div>型号</div> <div>PY-4</div> <div>PY-6</div> <div>PY-8</div> <div>PY-10</div> <div>PY-12</div>
<div>PEG T 型减径三通</div> <div></div>	<div>型号</div> <div>PEG-6/4</div> <div>PEG-8/6</div> <div>PEG-10/8</div> <div>PEG-12/10</div>	<div>PZA 十字四通</div> <div></div>	<div>型号</div> <div>PZA-4</div> <div>PZA-6</div> <div>PZA-8</div> <div>PZA-10</div> <div>PZA-12</div>
<div>SNSF 管道型</div> <div></div>	<div>型号</div> <div>SNSF-6</div> <div>SNSF-8</div> <div>SNSF-10</div> <div>SNSF-12</div>	<div>SL 直接安装 L 型</div> <div></div>	<div>型号</div> <div>SL-4/M5</div> <div>SL-4/01</div> <div>SL-4/02</div> <div>SL-6/M5</div> <div>SL-6/01</div> <div>SL-6/02</div> <div>SL-6/03</div> <div>SL-6/04</div> <div>SL-8/01</div> <div>SL-8/02</div> <div>SL-8/03</div> <div>SL-8/04</div> <div>SL-10/01</div> <div>SL-10/02</div> <div>SL-10/03</div> <div>SL-10/04</div> <div>SL-12/02</div> <div>SL-12/03</div> <div>SL-12/04</div>
<div>PM 隔板直通</div> <div></div>	<div>型号</div> <div>PM-4</div> <div>PM-6</div> <div>PM-8</div> <div>PM-10</div> <div>PM-12</div>		

4 订货须知

用户应正确填写下列内容：

- 4.1 产品名称、型号、规格；
- 4.2 订货数量；
- 4.3 如有特殊要求，可按非标产品订做。
- 4.4 订货示例：欲订购气管外径 8mm，接口螺纹 R1/4" 螺纹直通的接头 50 件。
示例如下：PC-8/02 50 件