

☐新申请 ☒变更 ☐监督 ☐复审 ☐其他

(任务编号)

产品名称: 交流接触器

型 号：

NC8-25□□/□□/□，
NC8-32□□/□□/□，
NC8-38□□/□□/□，
NC8-25□□/□□/□/□N，
NC8-32□□/□□/□□/□N，
NC8-38□□/□□/□□/□N

检测机构: 上海电器设备检测所有限公司



附页 1:

NC8-25□□/□□/□, NC8-32□□/□□/□, NC8-38□□/□□/□, NC8-25□□/□□/□/ N,
NC8-32□□/□□/□/ N. NC8-38□□/□□/□/ N

$U_{imp}: 6kV;$

$$U_i: 690V;$$

Ue: AC240(230/220)V, AC415(400/380)V, AC690(660)V;

NC8-25□□/□□/□, NC8-25□□/□□/□/□N:

lth:40A;

AC-1:AC240(230/220)V/40A,AC415(400/380)V/40A ,AC690(660)V/40A:

AC-3:AC240(230/220)V/25A,AC415(400/380)V/25A,AC690(660)V/17.3A:

AC-4:AC240(230/220)V/25A,AC415(400/380)V/25A,AC690(660)V/14A;

NC8-32□□/□□/□.NC8-32□□/□□/□/□:

lth:50A;

AC-1:AC240(230/220)V/50A,AC415(400/380) V/50A,AC690(660)V/50A;

AC-3:AC240(230/220)V/32A,AC415(400/380)V/32A,AC690(660)V/21.9A;

AC-4:AC240(230/220)V/32A,AC415(400/380)V/32A,AC690(660)V/17.3A:

NC8-38□□/□□/□, NC8-38□□/□□/□/□:

lth:50A;

AC-1:AC240(230/220)V/50A,AC415(400/380) V/50A ,AC690(660)V/50A;

AC-3:AC240(230/220)V/38A,AC415(400/380)V/38A,AC690(660)V/21.9A;

AC-4:AC240(230/220)V/38A,AC415(400/380)V/32A,AC690(/660)V/17.3A;

Us: AC24V,36V,42V,48V,110V,120V,127V,220V,230V,240V,277V,380V,400V,415V,
440V,460V,480V,600V,660V (50Hz):

AC24V,36V,42V,48V,110V,120V,127V, 220V,230V,240V,277V,380V,400V,415V,440V,
460V,480V,600V,660V (50/60Hz) ;

DC24V,48V,110V,125V,220V:

AC/DC24V~60V,48V~130V,100V~250V,50/60Hz;

极数: 3P,4P (4NO,2NO+2NC);

外壳防护等级: IP20 (仅适用于正前侧):

配用的辅助触头: (本体)

2NO2NC,1NO1NC,2NO,2NC,2NO1NC,1NO2NC,1NO,1NC;

Ith: 10A;

AC-15: Ue/Ie: AC380V/400V/415V/1.5A:

DC-13: Ue/Ie: DC220V/250V/0.3A

